



PREMIUM AFTERMARKET WIND DEFLECTORS

Porsche 911 (1985-1998) wind deflector installation instructions

Product No: 29.01.03.01



What is in the box

- 1 x Wind deflector
- 2 x Brackets
- 2 x washers
- 2 x Rotary knobs



Needed but not supplied by default:

2 x Installation plugs

Porsche Part No.: P00004320297.



Forgot to order the plugs?

Don't worry. Scan the QR code below to find them on our website!





PREMIUM AFTERMARKET WIND DEFLECTORS

Please read the instructions below carefully. You can also watch our installation video on YouTube. Please scan the QR code below.



STEP 1

Check if your car has the factory fitted wind defectors mounts. If your car does not have these mounts you can order these at your local Porsche dealer part no. P00004320297.



STEP 2

Open the top and fold the front and rear seats forward.





PREMIUM AFTERMARKET WIND DEFLECTORS

STEP 3

Place the wind deflector in the car and unfold the bottom bracket.



STEP 4

Push the side brackets into the opening of the wind deflector mounts. Tighten the knobs.





PREMIUM AFTERMARKET WIND DEFLECTORS

STEP 5

Attach the elastic straps to the eyelets which are located in the left and right corner behind the rear seats.



STEP 6

Fold the rear seats back up in normal (vertical) position.





PREMIUM AFTERMARKET WIND DEFLECTORS

Done!

Go out for a drive and enjoy your APERTA wind deflector!



Ask your APERTA dealer about the optional wind deflector holdall:

Luxury storage bag for your Porsche wind deflector.



Product No. WINDSCHIELDB

Specifications

- 2 x Velcro straps for wind deflector fixations
- Pocket for the wind deflector brackets and knobs
- Protective padding
- Zip fastener
- Made of high quality 1680D nylon
- 100% dust repellent
- Dimensions: 105 x 38 x 10 cm

TÜV SÜD Automotive GmbH
Gottlieb-Daimler-Straße 7
D-70794 Filderstadt



Automotive

Nr.: 002
Hersteller: Way Automotive Products BV
Typ: Windschott

Seite 1 von 1

Gutachterliche Stellungnahme

Betreff: Windschott für Kraftfahrzeuge (Cabrio)

Antragsteller: Way Automotive Products BV
Talhoutweg 7
NL – 8171MB Vaassen
Niederlande

Aufgabe:

Die Anbringung eines Windschotts mittels Klemm bzw. Schraubvorrichtung im Innenraum hinter den Vordersitzen von Kraftfahrzeugen ist zu beurteilen.

Beispiel:



Beurteilung:

Diese Fahrzeugteile sind einem Dachgepäckträger gleichzusetzen.

Gemäß Beispielkatalog zum §19 StVZO erlischt die Betriebserlaubnis eines Fahrzeug nicht durch die Anbringung eines Windschotts (siehe Punkt 6.21 des Beispielkatalogs) weil keine Genehmigung und / oder Teilegutachten erforderlich ist.

Dies gilt für Windschotts die die Vorschriften der StVZO erfüllen.

AM-HZBW; Filderstadt, den 26. 05. 2009,



Dipl.- Ing.(FH) Schwarz